The following listing of claims replaces all prior versions of claims in the application.

Claim 1 (Cancelled)

Claim 2 (Currently Amended): A device for storing an article for protecting an automobile body,

said device comprising:

a rotatable body comprising a first article and a second article,

[[a]] said first article, which is being disposed on said second article, and configured to

protect an exterior portion of the automobile body; and

[[a]] said second article, which surrounds surrounding an axis of rotation positioned

within the automobile body,

wherein said first article and said second article are attached to form a rotatable body,

which wherein said rotatable body rotates about said axis of rotation,

wherein said rotatable body having has a first position and a second position such that, in

said first position, said first article extends from the automobile body to protect the automobile

body, and, in said second position, said first article is concealed within the automobile body, and

wherein the rotating body must rotate rotates approximately 180 degrees to change its

position from said first position to said second position.

Claim 3 (Previously Presented): The device of claim 2, wherein said second article is

formed of the same material as the automobile body.

Page 2

Amendment under 37 CFR 1.114 Serial No. 10/540,935 Attorney Docket No. 052497

Claim 4 (Previously Presented): The device of claim 2, further comprising:

a switch, which is operative to activate electric power to rotate said rotating body between said first position and said second position,

wherein said switch is located inside the automobile.

Claim 5 (Previously Presented): The device of claim 2, further comprising:

a switch, which is operative to activate electric power to rotate said rotating body between said first position and said second position,

wherein said switch is a remote controller.

Claim 6 (Cancelled)

Claim 7 (Currently Amended): A device for storing an article for protecting an automobile body, said device comprising:

a rotatable body comprising a first article and a second article,

- [[a]] <u>said</u> first article, <u>which is being disposed on said second article</u>, <u>and</u> configured to protect an exterior portion of the automobile body; and
- [[a]] <u>said</u> second article, <u>which surrounds</u> <u>surrounding</u> an axis of rotation positioned within the automobile body,

wherein said first article and said second article are attached to form a rotatable body, which wherein said rotatable body rotates about said axis of rotation,

wherein said rotatable body having has a first position and a second position such that, in

said first position, said first article extends from the automobile body to protect the automobile

body, and, in said second position, said first article is concealed within the automobile body, and

wherein, with respect to a cross-section taken perpendicular to said axis of rotation, said

axis of rotation extends along the center of said second article.

Claim 8 (Previously Presented): The device of claim 7, wherein said second article is formed of

the same material as the automobile body.

Claim 9 (Previously Presented): The device of claim 7, further comprising:

a switch, which is operative to activate electric power to rotate said rotating body between

said first position and said second position,

wherein said switch is located inside the automobile.

Claim 10 (Previously Presented): The device of claim 7, further comprising:

a switch, which is operative to activate electric power to rotate said rotating body between

said first position and said second position,

wherein said switch is a remote controller.

Claim 11 (Cancelled)

Page 4